

Amendments to the Specification:

Please amend the specification as follows:

Page 1, after the Title, please insert the following paragraph:

This application is a National Stage application of PCT/KR 03/001990, filed September 30, 2003, which claims priority from Korean patent application 20-2002-0033087, filed November 5, 2002. The entire contents of each of the aforementioned applications are incorporated herein by reference.

Page 3, amend the paragraph on lines 10-11 as follows:

~~Fig. 5 shows a~~ Figs. 5 and 6 show side-sectional ~~view~~ views of ~~one portion~~ portions of the case showing an embodiment of the use of the piston according to the present invention.

Amend the paragraph beginning on page 5, line 21, and ending on page 5, line 8, as follows:

According to the present invention established as above, as shown in ~~Figs. 5a and 5b~~ Figs. 5 and 6, if the content is exhausted into the outside of the case (300) after the screw pillar (100) is removed to the center of case because if required, the piston assembly (200) is placed more than one or two to the inner portion of the case (300), the piston(210) is removed by the screw cap (220) that the screw hole (222) is connected with the screw (112) of the screw pillar (100) and also the sealing washer (230) that is elastically placed between the piston (210) and the screw cap (220) is removed as such the state that the chink that is generated between the screws (112) of the screw pillar (100) is certainly sealed and even if the content is poured through the penetrating hole (212) of the piston (210), it can certainly prevent that the content is spilled to the chink that is generated between the piston (210) and the screw cap (220) because the inner portion of the piston assembly (200) is entirely sealed by the sealing washer (230).